




widescreen




widescreen

	Model	MT6050iV3	MT6070iH3
Display	Display	4.3" TFT	7" TFT
	Resolution	480x272	800x480
	Brightness (cd/m ²)	300	350
	Contrast Ratio	500:1	500:1
	Backlight Type	LED	LED
	Backlight Life Time	30,000 hr	30,000 hr
Touch Panel	Type	4-wire Resistive Type	
Enclosure		Plastic	
Memory	Storage (MB)	128	128
	RAM (MB)	64	64
Processor		RISC 400MHz	RISC 400MHz
I/O Port	SD Card Slot	N/A	N/A
	USB Host	N/A	USB 1.1 x 1
	USB Client	USB 2.0 x 1	USB 2.0 x 1
	Ethernet	N/A	N/A
	COM Port	COM1 (RS232 / RS485 2W/4W).COM3 (RS485 2W)	COM1 (RS232 / RS485 2W/4W),COM2 (RS232) COM3 (RS232 / RS485 2W)
	Audio	N/A	N/A
RTC		N/A	Yes
Power	Input Power	24±20% VDC	24±20% VDC
	Power Consumption	250mA@24V	250mA@24V
Specification	Panel Cutout (mm)	119x93	192x138
	Weight (kg)	0.3	0.85
Operation	Protection Structure	IP65 front panel(O ring seal)	IP65 front panel (O ring seal)
	Storage Temperature	-20°~60°C (-4°~140°F)	-20°~60°C (-4°~140°F)
	Operating Temperature	0°~50°C (32°~122°F)	0°~50°C (32°~122°F)
Certification		EN 55022:2006,Class A .EN 61000-3-2:2006 .EN 61000-3-3:1995+A1:2001+A2:2005 EN 55024:1998+A1:2001+A2:2003	


MT6050iV3




Front View



Rear View




Bottom View




Panel Cutout

MT6070iH3



Front View



Rear View



Bottom View



Panel Cutout



WEINTEK LABS., INC. | www.weintek.com

Email: servicemail@weintek.com

TEL: (886)2-22286770

Address: 9F., No.910, Zhongzheng Rd.,
Zhonghe Dist., New Taipei City 23586, Taiwan